

## Dorsal/Lateral Cylinder Base Equine Table

The Shank's® Dorsal/Lateral Cylinder Base Equine Table was introduced in 1988 and was specifically designed for the equine surgeon. It is equipped with 4-way tilt capability and can easily support an animal in dorsal or lateral recumbency via the innovative design of the wing-style sectioned table top. **The entire table structural frame can be fabricated from stainless steel as a customization.**

### Technical Specs

- 46" x 84" lateral surface area (117cm x 213cm)
- 18" x 84" center bed (46cm x 213cm)
- Six hinged fold up wings (both center wings completely removable)
- 6" swivel casters (removable)
- Self-contained power unit (available 110V/60 cycle or other power configurations for international use)
- Hand control hydraulic valve (6 functions)
- 4-way hydraulic tilt capability
- Versatile wing-style supports for both dorsal and lateral positioning of animal
- Lowered height 22-1/2" (57cm)
- Raised height 39" (99cm)
- Hot dip galvanized coating/enamel topcoat
- Stainless steel fasteners & motor shield
- Rated for 2,500 lbs. (1,134 kg)

### Standard Accessories

- Flat extension (22" x 26"/56cm x 66cm)
- Set of four dorsal leg poles & tie loops
- Leverage bar
- Square tube offset bracket (for offset placement of flat head extension)

### Optional Accessories/Features

- XL Table Top size -62" x 84" (157cm x 213cm)
- V-head extension
- SS intestinal tray (table mount)
- SS intestinal tray with free standing base
- Lateral arthroscopic leg bracket
- Simple lateral bracket
- Dorsal arthroscopic leg bracket (pair)
- Small Flat (8" x 16" / 20cm x 41cm)

- Medium Flat (12" x 20" / 30cm x 51cm)
- SS IV Pole (with or without breathing circuit support)
- Round tube cross pipe
- D/L removable step
- Bilateral hind limb support
- T-handle
- D/L storage cart
- Foam positioning pads
- Lifting hobbles

### Hydraulic System and Operation

The Table is user friendly and merely requires access to power for operation. Once the table is connected to power, an on/off switch turns on the hydraulic system. The four outside cylinders run individually or in combinations and can be manipulated to achieve 4-way tilt. The inside cylinders run in pairs. The Table is raised and lowered by manipulation of the hand control levers mounted on the table. The table can be stopped at any position during raising or lowering. The remaining two handles allow for independent retraction of the casters on the head and tail end of the table.

All optional accessories are easily connected to the table by inserting them into any of the table ports located around the perimeter of the table top. The optional accessories allow for both dorsal and lateral support.

